



## K005 DYMA WAX FREE POLISH (2)

### 1. IDENTIFICATION OF THE PREPARATION AND COMPANY

PRODUCT CODE: K005  
PRODUCT NAME: DYMA WAX FREE POLISH (2)  
MANUFACTURER: Selden Research Limited  
Staden Lane  
Ashbourne Road  
Buxton  
Derbyshire  
SK17 9RZ

TELEPHONE: 01298 26226  
FAX: 01298 26540  
EMAIL: [safety@selden.co.uk](mailto:safety@selden.co.uk)

### 2. HAZARDS IDENTIFICATION

R12 Extremely flammable.

PRESSURISED CONTAINER - increase in temperature to greater than 50C will cause internal pressure to rise potentially causing bursting/explosion.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

NAME CAS No.:	EINECS Nr.:	CLASSIFICATION	CONTENT
ALIPHATIC DISTILLATE 64742-48-9	265-150-3	Xn;R65. R10,R66.	5-10 %
BUTANE 106-97-8	203-448-7	F+;R12	10-30 %
KEROSENE - NARROW CUT - NON AROMATIC 64742-47-8		Xn;R65. R66.	5-10 %

The full text for all R-Phrases are displayed in Section 16

### 4. FIRST AID MEASURES

**INHALATION:** Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention. For breathing difficulties oxygen may be necessary.

**INGESTION:** Rinse mouth thoroughly. Drink plenty of water. Get medical attention.

**SKIN:** Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

**EYES:** Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

### 5. FIRE FIGHTING MEASURES

**EXTINGUISHING MEDIA:** Use: , Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

**SPECIAL FIRE FIGHTING PROCEDURES:** Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

**UNUSUAL FIRE & EXPLOSIVE HAZARDS:** Aerosol cans may explode in a fire.

### 6. ACCIDENTAL RELEASE MEASURES

**SPILL CLEAN UP METHODS:** Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. If leakage cannot be stopped, evacuate area.

**ENVIRONMENTAL PRECAUTIONS:** Any spillage needs to be contained and not allowed to enter water courses

### 7. HANDLING AND STORAGE

**USAGE PRECAUTIONS:** Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

**STORAGE PRECAUTIONS:** Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.



# K005 DYMA WAX FREE POLISH (2)

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

INGREDIENT NAME:	CAS No.:	STD	LT EXP 8 Hrs	ST EXP 15 Min
BUTANE		WEL	1450 mg/m3	1810 mg/m3

### PROTECTIVE EQUIPMENT:



## 9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Aerosol
COLOUR:	White
ODOUR:	Strong fragrant (Leather/Lavender type)
PHYSICAL DATA COMMENTS:	Information given relates to total aerosol container contents.
DENSITY/SPECIFIC GRAVITY(g/ml)	0.803
FLASH POINT (°C):	- 74 N/A.
AUTO IGNITION TEMPERATURE (°C):	+ 405
FLAMMABILITY LIMIT - LOWER(%):	1.8
FLAMMABILITY LIMIT - UPPER(%):	10.0

## 10. STABILITY AND REACTIVITY

STABILITY:	Stable under normal temperature conditions.
CONDITIONS TO AVOID:	Avoid heat, flames and other sources of ignition. Increase in temperature to greater than 50 degrees will cause rise in internal pressure with likelihood of bursting/explosion.
HAZARDOUS COMPOSITION PRODUCTS:	Fire creates:, Toxic gases/vapours/fumes of:, Carbon monoxide (CO). Carbon dioxide (CO2).

## 11. TOXICOLOGY INFORMATION

INHALATION:	High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting. Gas or vapour displaces oxygen available for breathing (asphyxiant). Unconsciousness.
SKIN CONTACT:	No specific health warnings noted.
EYE CONTACT:	Irritation of eyes and mucous membranes.

## 12. ECOLOGICAL INFORMATION

ECOTOXICITY:	Not classed as Hazardous to the Environment but release to the environment should be avoided.
--------------	---

## 13. DISPOSAL CONSIDERATIONS

DISPOSABLE METHODS:	Empty containers must not be burned because of explosion hazard., Dispose of waste and residues in accordance with local authority requirements.
---------------------	--

## 14. TRANSPORT INFORMATION

UN No ROAD:	1950
UK ROAD TRANSPORT CLASS:	-
ADR CLASS NO.:	2.1
PROPER SHIPPING NAME I:	AEROSOLS, FLAMMABLE
UN No SEA:	1950
IMDG CLASS:	2.1
UN NO. AIR:	1950
ICAO CLASS:	2.1



# K005 DYMA WAX FREE POLISH (2)

## 15. REGULATORY INFORMATION

LABEL FOR SUPPLY:



RISK PHRASES:

R12 Extremely flammable.

SAFETY PHRASES:

S2 Keep out of the reach of children, S16 Keep away from sources of ignition - No smoking, S23 Do not breathe vapour/spray, S51 Use only in well-ventilated areas.

STATUTORY INSTRUMENTS:

Control of Substances Hazardous to Health. Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE:

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES:

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

## 16. OTHER INFORMATION

USER NOTES:

The following risk phrases relate to the raw materials in the product and not the product itself:-

REVISION DATE:

05/04/2006

REV. NO./REPL. SDS GENERATED:

13

R-PHRASES (Full Text):

R12 Extremely flammable.| R10 Flammable., R66 Repeated exposure may cause skin dryness or cracking., R65 Harmful: may cause lung damage if swallowed.| R66 Repeated exposure may cause skin dryness or cracking., R65 Harmful: may cause lung damage if swallowed.|